SCHOOL OF PLANNING AND ARCHITECTURE, VIJAYAWADA

SEMESTER END EXAMINATIONS (REGULAR), MAY-2016

B. ARCH, III YEAR, VI SEMESTER

BUILDING MANAGEMENT (BM-6) (QUANTITIES AND ESTIMATIONS)

Maximum Marks - 60

Mason

Men Mazdoor

Women Mazdoor

Mixing Charges

Rs. 400/day

Rs. 350/day

Rs. 350/day

Rs. 60 Cum

a) Answer any Two questions out of 1to 4 questions.

Time - 2 1/2 Hours

	ame Sundote unia, ij	necessary.										
Q1.	a) Define the terms est	imation and Specifications.			(5M)							
×	b) Write the Units of measurement of the following items of work											
	i) Earth work ii) RCC iii) Sand Filling											
	iv) Plastering v) Sunshade											
	c) The Plan and Section of steps are given in Fig. 0. Calculate the quantity of C.C (1:4:8) steps, calculate the quantity of brick masonry required for steps.											
								Q2.	a) State and define different approximate methods of estimating engineering structures. (5M)			
	~	b) Write the difference between detailed estimate and abstract estimate?										
c) Prepare the approximate estimate of a proposed building with the following data (5M)												
a) Plinth area		= 400 Sg m		# D								
	 b) Plinth area rat 	te = Rs. 25000 per Sq.	m .	Ŕ.								
	c) Water Supply	and Sanitation = 12% of the cost of	f building	- E-1	(10M							
	d) Electrification = 7.5% of cost of Building											
	e) Fluctuation of	frates = 3% of cost of buil	ding									
00	75 4 1 2 1 1		16 131 1 16 2	0								
Q3.,		timate for the following items of wor		.0	(1034							
	a) K.K masonry i	in C.M (1:6) for Footings and baseme	ent.		(10M)							
	15 15 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	ONE (1.6) C. C C			2500							
		C.M (1:5) for Super Structure	<u>\$</u>		(5M)							
		C.M (1:5) for Super Structure Ceiling with C.M (1:3)	je in the second		(5M) (5M)							
O4.	c) Plastering to C	Ceiling with C.M (1:3)										
Q4.	c) Plastering to C	Ceiling with C.M (1:3) and calculate the cost of items given be			(5M)							
Q4.	c) Plastering to C Prepare a data sheet ar a) CC (1:5:10) using	Ceiling with C.M (1:3) and calculate the cost of items given be g 40mm HBG metal – 1 cum			(5M)							
Q4.	c) Plastering to C Prepare a data sheet ar a) CC (1:5:10) using b) RR masonry in C	Ceiling with C.M (1:3) and calculate the cost of items given be g 40mm HBG metal – 1 cum CM (1:4) – 1 cum										
Q4.	c) Plastering to C Prepare a data sheet ar a) CC (1:5:10) using b) RR masonry in C Materials and Labour	Ceiling with C.M (1:3) and calculate the cost of items given be g 40mm HBG metal – 1 cum CM (1:4) – 1 cum required:			(5M)							
Q4.	c) Plastering to C Prepare a data sheet ar a) CC (1:5:10) using b) RR masonry in C Materials and Labour CC (1:5:10) using 40n	Ceiling with C.M (1:3) and calculate the cost of items given be g 40mm HBG metal – 1 cum CM (1:4) – 1 cum required: nm HBG metal – 1 cum			(5M)							
Q4.	c) Plastering to C Prepare a data sheet ar a) CC (1:5:10) using b) RR masonry in C Materials and Labour CC (1:5:10) using 40n 0.92m ³	Ceiling with C.M (1:3) and calculate the cost of items given be g 40mm HBG metal – 1 cum CM (1:4) – 1 cum required: nm HBG metal – 1 cum 40mm HBG metal			(5M)							
Q4.	c) Plastering to C Prepare a data sheet ar a) CC (1:5:10) using b) RR masonry in C Materials and Labour CC (1:5:10) using 40n 0.92m³	Ceiling with C.M (1:3) and calculate the cost of items given by g 40mm HBG metal – 1 cum CM (1:4) – 1 cum required: nm HBG metal – 1 cum 40mm HBG metal Sand			(5M)							
Q4.	c) Plastering to C Prepare a data sheet ar a) CC (1:5:10) usin; b) RR masonry in C Materials and Labour CC (1:5:10) using 40n 0.92m³	Ceiling with C.M (1:3) and calculate the cost of items given be g 40mm HBG metal – 1 cum CM (1:4) – 1 cum required: nm HBG metal – 1 cum 40mm HBG metal Sand Cement			(5M)							
Q4.	c) Plastering to C Prepare a data sheet ar a) CC (1:5:10) using b) RR masonry in C Materials and Labour CC (1:5:10) using 40n 0.92m³	Ceiling with C.M (1:3) Indicalculate the cost of items given be g 40mm HBG metal – 1 cum required: Indicalculate the cost of items given be g 40mm HBG metal – 1 cum 40mm HBG metal Sand Cement Mason			(5M)							
Q4.	c) Plastering to C Prepare a data sheet ar a) CC (1:5:10) using b) RR masonry in C Materials and Labour CC (1:5:10) using 40n 0.92m³ 0.2 Nos. 1.80 Nos.	Ceiling with C.M (1:3) and calculate the cost of items given be g 40mm HBG metal – 1 cum 2M (1:4) – 1 cum required: and HBG metal – 1 cum 40mm HBG metal Sand Cement Mason Man Mazdoor			(5M)							
Q4.	c) Plastering to C Prepare a data sheet ar a) CC (1:5:10) using b) RR masonry in C Materials and Labour CC (1:5:10) using 40n 0.92m³	Ceiling with C.M (1:3) and calculate the cost of items given be g 40mm HBG metal – 1 cum 2M (1:4) – 1 cum required: and HBG metal – 1 cum 40mm HBG metal Sand Cement Mason Man Mazdoor Women Mazdoor			(5M)							
Q4.	c) Plastering to C Prepare a data sheet ar a) CC (1:5:10) using b) RR masonry in C Materials and Labour CC (1:5:10) using 40n 0.92m³	Ceiling with C.M (1:3) and calculate the cost of items given be g 40mm HBG metal – 1 cum CM (1:4) – 1 cum required: and and and and and and and a			(5M)							
Q4.	c) Plastering to C Prepare a data sheet ar a) CC (1:5:10) using b) RR masonry in C Materials and Labour CC (1:5:10) using 40n 0.92m³	Ceiling with C.M (1:3) and calculate the cost of items given be g 40mm HBG metal – 1 cum CM (1:4) – 1 cum required: and and and and and and and a			(5M)							
Q4.	c) Plastering to C Prepare a data sheet ar a) CC (1:5:10) usin; b) RR masonry in C Materials and Labour CC (1:5:10) using 40n 0.92m³ 0.2 Nos. 1.80 Nos. 1.40 Nos. 1.5 RR masonry in Cm (1 1.1 Cum	Ceiling with C.M (1:3) and calculate the cost of items given by g 40mm HBG metal – 1 cum CM (1:4) – 1 cum required: nm HBG metal – 1 cum 40mm HBG metal Sand Cement Mason Man Mazdoor Women Mazdoor Sundries :4) – 1 Cum Rough Stone			(5M)							
Q4.	c) Plastering to C Prepare a data sheet ar a) CC (1:5:10) using b) RR masonry in C Materials and Labour CC (1:5:10) using 40n 0.92m³	Ceiling with C.M (1:3) and calculate the cost of items given be g 40mm HBG metal – 1 cum CM (1:4) – 1 cum required: and and and and and and and a			(5M)							
Q4.	c) Plastering to C Prepare a data sheet ar a) CC (1:5:10) usin; b) RR masonry in C Materials and Labour CC (1:5:10) using 40n 0.92m³ 0.2 Nos. 1.80 Nos. 1.40 Nos. 1.5 RR masonry in Cm (1 1.1 Cum 0.34 Cum	Ceiling with C.M (1:3) and calculate the cost of items given be g 40mm HBG metal – 1 cum CM (1:4) – 1 cum required: nm HBG metal – 1 cum 40mm HBG metal Sand Cement Mason Man Mazdoor Women Mazdoor Sundries :4) – 1 Cum Rough Stone CM (1:4)			(5M)							
Q4.	c) Plastering to C Prepare a data sheet ar a) CC (1:5:10) usin; b) RR masonry in C Materials and Labour CC (1:5:10) using 40n 0.92m³ 0.2 Nos. 1.80 Nos. 1.40 Nos. L.S RR masonry in Cm (1 1.1 Cum 0.34 Cum 1.8 Nos.	Ceiling with C.M (1:3) and calculate the cost of items given be g 40mm HBG metal – 1 cum CM (1:4) – 1 cum required: nm HBG metal – 1 cum 40mm HBG metal Sand Cement Mason Man Mazdoor Women Mazdoor Sundries :4) – 1 Cum Rough Stone CM (1:4) Mason			(5M)							

S.No	Materials	Rate at Source	Lead in Km	Conveyance Charges
1	40mm HBG metal	1200/Cum	10MT + 8ST	18 /Cum/Km
	Sand	600/Cum	20MT + 5CT	16/Cum/Km
3	Rough Stone	150/Cum	5MT + 5ST	15/Cum/Km
4	Cement	7500/MT	At Site	

Q5. a) Calculate the quantity of Cement required in bags for the following items of work:

(4x5=20M)

i) C.C 1:4:8 work for Plain Concrete work using 40mm HBG metal for 20m³ of work.

(2.5Marks)

REPRESENT.

ii) Brick masonry in CM 1:6 using Country bricks for 20m³ of work, if 0.5m³ mortar is required for 1m³ of masonry

(2.5Marks)

b) State the methods of taking out quantities & briefly explain them

c) State the technical team involved in the estimation

d) List the provision for different building services as percentage of Structure Cost

e) For a hipped roof shown in the Fig 3.0, Calculate

a) Length of hip rafer

(2.5 Marks)

b) No. of Common rafer Spaced at 500'MM c/c NOTE: Wall Thickness = 300mm

(2.5 Marks)

Eaves Projection = 500mm

Rise of roof = 1700 mm

f) The internal dimensions of a room are 6.25 x 4.25m. Find the quantity of Sand filling in basement. The height & thickness of basement are 750mm & 450mm respectively. The wall thickness of room is 230mm.